

Premium performance in an ultra-compact design





Advanced Compression

Our patented compression system ensures even toasting without bun crushing



Programmable Settings

Customize toast times and temperatures for any bread



User-Friendly Interface

The color LCD screen simplifies operations



types with ease.

Designed for compact spaces, the CTD contact toaster from Prince Castle is packed with gold-standard features, combining precision and top performance to bring unparalleled toast quality to even

the smallest kitchens. Its innovative design allows operators

to work more efficiently, accomodating a wide range of bread



Toasting Consistency

Heavy-duty platen retains heat, ensuring perfect toast all day

Product Highlights

CTD

Ultra-compact, versatile, and built for modern kitchens, the CTD is the ideal partner for delivering quality at speed. Engineered for fast, repeatable results, it helps streamline operations while maintaining the best-in-class excellence that your customers expect.





Compact footprint

Optimized for small spaces without compromising quality.



Advanced technology

Patented compression for perfect caramelization.



Effortless control Intuitive navigation between pre-programmed settings.

3

ELEVATE QUALITY AND REDUCE WASTE

- Patented compression technology ensures perfect caramelization without crushing.
- Delivers consistent, best-in-class results across all bread types.
- Advanced heating technology reduces waste and ensures precision toasting during peak demand.
- Ultra-compact design fits small kitchens effortlessly.

SIMPLIFIED OPERATIONS

- Intuitive LCD touchscreen for crew-friendly operation and programming.
- Pre-programmed settings minimize user error during busy hours.
- Durable construction ensures reliability in demanding environments.
- One-handed bun-feeding improves throughput during peak times.
- Fits seamlessly into any kitchen workflow

MENU FLEXIBILITY

- Adjustable toasting times (6-40 seconds) for peak customization.
- Accommodates various bread types, from artisan loaves to standard buns.
- Programmable daypart settings streamline menu transitions.
- Auxiliary heat option enhances toasting quality for premium sandwiches.

EASY TO CLEAN

- Stainless steel construction for quick, hassle-free cleaning.
- Non stick release sheets prevent residue build-up ensuring lasting, optimal toaster performance.
- Detachable conveyor belts simplify cleaning.
- Easy component access ensures efficient upkeep.

SUSTAINABILITY

- Energy-efficient auxiliary heaters reduce operational costs.
- Long-lasting components minimize waste and reduce replacements.
- Compact footprint lowers overall kitchen energy consumption.
- Heat-shield design ensures cooler surfaces for safety, while enhancing energy efficiency.





Technical Specifications

CTD - Contact Toaster Dual Sided


Output & Electrical

Model N	° Description	Volts	Hz	Watts	Amps	Plug	Tempera- ture range	Bread diameter	Varialble speed	Pass through time	Belt
CTD-SA)	Dual sided toaster, Silicone belt w/Aux heater	208-240	60	1700- 2250	8.1- 9.4	NEMA L6-20P	100-550°F 38-288°C	5.5" 14cm	Yes	6-40 sec	Silicone
CTD-SAX	Dual sided toaster, Silicone belt w/Aux heater, CE	220-240	50/60	1650- 2000	8.6- 9.4	CEE 7.7	100-550°F 38-288°C	5.5" 14cm	Yes	6-40 sec	Silicone

Product Dimensions + Weight Specifications

Width	12.0" (30,5cm)			
Depth	10.8" (27,4cm)			
Height	21.3" (54,1cm)			
Unit Weight	51 lbs (23,1kg)			
Shipping Weight	56 lbs (25,4kg)			





Accessories

Model Number	Description
511-142	Butter Wheel
301-156s	Replacement Release Sheet Kit
301-137S	Silicone Belt 2 pack

Certifications









Whatever your needs, we've got the right solution for every toasting occasion.













Model	297-T9	297-T12P	297-T20	стѕ	СТД	CTDE	
Toaster Style	Contact, Continuous	Contact, Continuous	Contact, Continuous	Contact, Continuous	Contact, Continuous	Contact, Continuous	
Unit Dimensions							
Width (in)	25.0"	25.0"	25.0"	20.3"	12.0"	17.5"	
Depth (in)	8.2"	8.2"	8.2"	8.5"	10.8"	10.8"	
Height (in)	26.3"	26.3"	26.3"	22.2"	21.3"	21.3"	
Net Weight (lbs.)	71 lbs.	71 lbs.	71 lbs.	65 lbs.	51 lbs.	70 lbs.	
Shipping Dimensions							
Width (in)	26.0"	26.0"	26.0"	24.5"	16.5"	21.8"	
Depth (in)	12.2"	12.2"	12.2"	13.0"	16.3"	15.8"	
Height (in)	27.6"	27.6"	27.6"	27.0"	28.3"	21.1"	
Shipping Weight (lbs.)	82 lbs.	82 lbs.	82 lbs.	68 lbs.	56 lbs.	75 lbs.	
Bun Specifications							
Bread Diameter (in)	5.5"	5.5"	5.5"	5.5"	5.5"	5.5"	
Crown Min (in)	0.75"	0.75"	0.75"	0.5"	0.4"	0.4"	
Crown Max (in)	1.25"	1.25"	1.25"	1.25"	1.25"	1.25"	
Heel Min (in)	0.5"	0.5"	0.5"	0.3"	0.3"	0.3"	
Heel Max (in)	1.0"	1.0"	1.0"	1.0"	1.0"	1.0"	
Buns per Hour	2,400/hr	2,400/hr	2,400/hr	1,200/hr	1,200/hr	2,400/hr	
Product Specifications							
Platen	Single Sided	Single Sided	Single Sided	Single Sided	Dual Sided	Dual Sided	
Belt	Wire	Wire	Wire	Wire, Silicone	Silicone	Wire, Silicone, Stainless steel	
Variable Speed	No	No	No	Yes	Yes	Yes	
Temp Range	370-570°F	370-570°F	370-570°F	100-550°F	100-550°F	100-550°F	
Pass Through Time	9 sec	12 sec	20 sec	9-40 sec	6-40 sec	6-40 sec	
Volts	115V	115V	115V	115V	208-240V	208-240V	
Hertz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	
Watts	1550W	1550W	1550W	1550W	1700-2250W	2440-3250W	
Amps			15.5	15.5	8.1-9.4	11.7-13.5	
Plug	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA 5-15P	NEMA L6-20P	NEMA L6-20P	
Warranty	1-Year Parts & Labor	1-Year Parts & Labor	1-Year Parts & Labor	1-Year Parts & Labor	1-Year Parts & Labor	1-Year Parts & Labor	
Accessories		Butter Wheel, Release Sheet Kit	Butter Wheel, Release Sheet Kit	Silicone Belt	Silicone Belt	Release Sheet Kit Silicone Belt	
Agency Listings	UL Safety, UL Sanitation, CE, EAC, UKCA	UL Safety, UL Sanitation, CE, EAC	UL Safety, UL Sanitation, CE, EAC	UL Safety, UL Sanitation, CE, EAC, UKCA	ELT Safety, ELT Sanitation, CE, EAC, UKCA	ELT Safety, ELT Sanitation, CE, EAC, UKCA	



PRINCECASTLE

The perfect toast, every time.









To learn more about Prince Castle toasters, visit *princecastle.com*To contact a Prince Castle representative, go to *princecastle.com/contact/*

355 E. Kehoe Blvd. Carol Stream, IL 60188 1.800.PCASTLE • 1.800.722.7853 - 630.462.8800

